

Get / Add MasterData's Values

Deskera Development Space

Exported on 12/18/2019

Table of Contents

1	GET/ Get MasterData's values	3
1.1	Get MasterData's values	3
2	POST/ Add MasterData's Value.....	5
2.1	Add Value to Custom Column.....	5

1 GET/ Get MasterData's values

Let's look at example – Getting all value's for a particular MasterData.

1.1 Get MasterData's values

v1/company/masterdata

ex:<REST_ERP_ENDPOINT>/rest/v1/company/masterdata?token=ABC

Request Method

GET

Request :

Parameters	Required/Optional	Description
companyid / cdomain	Required	Company Id / Subdomain
name	Required	MasterData name
token	Required	Please refer Apps - REST Services ¹

Response :

Field	Type	Description						
success	Boolean	Success (true / false)						
values	JSONArray	JSONObjects containing below fields: <table><tr><th>Key</th><th>Value</th></tr><tr><td>id</td><td>MasterData's value's Id</td></tr><tr><td>value</td><td>MasterData's value</td></tr></table>	Key	Value	id	MasterData's value's Id	value	MasterData's value
Key	Value							
id	MasterData's value's Id							
value	MasterData's value							

¹ <http://confluence.deskera.com/display/DEV/Apps+-+REST+Services>

Sample Request

```
{
  "cdomain": "abmalaysia",
  "name": "Relation"
}
```

Sample Response

```
{
  "success": true,
  "values": [
    {
      "id": "2a74ffee-a4f1-4919-8cec-dd4ebfdc8824",
      "value": "Girlfriend"
    },
    {
      "id": "36023130-31a1-4965-81c9-2782069d9514",
      "value": "Cousin"
    },
    {
      "id": "39804e35-67ef-4da7-9722-ae46bfdac112",
      "value": "checking"
    },
    {
      "id": "3b584f09-6f2a-4c7d-871d-3cd33620fa68",
      "value": "Wife"
    },
    {
      "id": "542b38d2-f2f6-46ec-b2e7-115daa9a71e0",
      "value": "Uncle"
    },
    {
      "id": "e1b924eb-99e7-4add-942a-613ab01a3895",
      "value": "Husband"
    }
  ]
}
```

2 POST/ Add MasterData's Value

Let's look at example – Add new value to the MasterData

2.1 Add Value to Custom Column

v1/company/addmasterdata

ex:<REST_ERP_ENDPOINT>/rest/v1/company/addmasterdata?token=ABC

Request Method

POST

Parameters	Required/Optional	Description
companyid / cdomain	Required	Company Id / Subdomain
masterdata	Required	MasterData's name
value	Required	Value to be added to MasterData
token	Required	Please refer Apps - REST Services ²

Sample Request

```
{
  "cdomain": "abmalaysia",
  "masterdata": "Relation",
  "value": "Father"
}
```

Sample Response

```
{
  "success": true
}
```

² <http://confluence.deskera.com/display/DEV/Apps+-+REST+Services>